

Equipment/Performance Features	Standard	Option
409 Stainless Steel Construction in Tower and Mechanical Assembly	S	
48" (1220mm), Lifting Height From Floor To Floor	S	
72" (1829mm), 96" (2439mm), 120" (3048mm), 144" (3658mm), 168" (4267mm) Lifting Height From Floor To Floor (maximum individual model lifting heights)		O
Aluminum Framed Enclosure in gloss powder baked enamel paint with aluminum inserts	S	
Rated Speed of 15' Per Minute (0.075m/sec.)	S	
1:2 Cable Hydraulic Drive System	S	
1 HP 24 Volt DC Motor	S	
750lb (340kg) Capacity Rating	S	
24 Volt DC Solid State Electronic Controller	S	
Power Requirement: 110 Volts, 1 Phase, 15 Amps	S	
Battery Backup Operation in Both Up and Down Directions	S	
Automatic Battery Recharging System	S	
Slack Cable Safety Device	S	
Lower and Upper Limit Switches with Final Limit	S	
Manual Lowering Device (Keyed)	S	
Negative Pressure Switch	S	
One Can of Architectural White Touch Up Paint	S	
Additional Cans of Architectural White Touch Up Paint	S	
Custom Powder Coating Color		O
3 Stop Configuration		O
Fasteners for Mounting Tower to Wall - Lag Bolts or Through Bolts		O
Fasteners for Mounting Tower Base to Concrete		O
Cab and Accessory Features	Standard	Option
36"W x 48"L (914mm x 1220mm) Type 2	S	
36"W x 54"L (914mm x 1372mm) Type 1, 2, 3 or 4		O
36"W x 60"L (914mm x 1524mm) Type 1, 2, 3 or 4		O
42"W x 60"L (1067mm x 1624mm) Type 3 or 4		O
43.375" (1073mm) High Cab Walls	S	
Aluminum Framed Cab Panels with Aluminum Inserts and Baked Polyester Powder Coat in Architectural White	S	
Anti-Skid Flooring on Platform and Ramp	S	
Automatic Emergency Platform Lighting	S	
Underpan Safety Sensor	S	
Automatic Flip-up 16" (406mm) Entrance Ramp	S	
Bottom Floor Permanent Ramp 8:1 or 12:1 ratio (Enclosed No Pit)		O
Constant Pressure Directional Push Buttons on Car Station Control	S	
Key Operated On/Off Switch on COP	S	
Handsfree Telephone		O
Emergency Stop Switch and Audible Alarm Button on COP	S	
409 Stainless Steel Hand Rail 1.25" (32mm) OD Mounted on Control Side Cab Panel	S	
Under Platform Safety Prop or Shoring Blocks		O

Optional Gate, Door, Accessibility & Enclosure Features	Standard	Option
Choice of clear plexi, bronze plexi, clear tempered glass or clear safety laminated glass inserts		○
Sloped or Dome Roof package for outdoor protection		○
Thermostatically controlled ventilation kit		○
Motion Sensor Lighting Package		○
43.375"H x 36"W (1073mm x 914mm) Platform Gate with Aluminum or Plexiglass Insert, Includes Kwiklock		○
43.375"H x 36"W (1073mm x 914mm) Landing Gate with Aluminum, Plexiglass (Clear or Bronze) or Tempered Glass Insert, Includes Kwiklock		○
43.375"H x 43.375"W (1073mm x 1073mm) Landing Gate with Aluminum, Plexiglass (Clear or Bronze) or Tempered Glass Insert, Includes Kwiklock		○
Custom Landing Gate 36"W (890mm) up to 84"H (2134mm), Includes Kwiklock		○
Custom Landing Gate 42.25"W (890mm) up to 84"H (2134mm), Includes Kwiklock		○
36" W x 91.375"H (890mm x 2292mm) Door with Plexiglass or Tempered Glass Insert, Includes Kwiklock		○
Wing Walls		○
Pro Manual Fire Rated Door with Prolock Interlock		○
Pro Auto Fire Rated Door with Integral Door Opener and Prolock Interlock		○
Commander Automatic Door Opener		○
Automatic Gate Opener (P.A.L. Door/Gate Only)		○
Hall Call Station Flush Mounted In Frame (not available with ProDoors), Keyed, Keyless, Call/Send, Call Only		○
Hall Call Station Flush Mounted Remote. Keyed, Keyless, Call/Send, Call Only		○
Hall Call Station Surface Mounted. Keyed, Keyless, Call/Send, Call Only		○
Interlocks – Kwiklock, Prolock, GAL		○