



PROLIFT SCL™
Standard Commercial Lift
Features & Options Summary
 Effective April 1, 2004

Equipment/Performance Features	Standard	Option
1:2 Cable Hydraulic Drive System	S	
2 Stop Package	S	
3 - 4 Stop Package		O
Rated Speed 30 fpm / 0.15mps (Nominal)		
Capacity - 1000lb / 454kg	S	
Capacity - 750lb / 340kg or 550lb / 250kg		O
Up to 10' (3048mm) of Total Travel	S	
10' to 40' (3048 mm to 12192 mm) of Total Travel		O
Travel Over 10' (3048mm) [Includes Hydraulics, Travelling Cable, Hoist Ropes & Rail (Per Foot)]		O
Power Required 230 Single Phase or 208 3-Phase 60Hz	S	
Pit Depth 8" (up to 24")	S	
Pit Depth 25" - 36"		O
Battery Operated Emergency Lowering and Lighting with Automatic Recharging	S	
Cab/Entrance Features	Standard	Option
Type 1 (Standard) or Type 2 Cab	S	
Type-3 Cab		O
Type-4 Cab		O
Type-5(S) Cab		O
Cab Height 80" (2032 mm) (Nominal)	S	
35" x 48" (889 mm x 1219 mm) Clear Inside	S	
35" x 54" (889 mm x 1371 mm) Clear Inside	S	
35" x 60" (889 mm x 1524 mm) Clear Inside	S	
Automatic Cab Lighting On/Off	S	
Vertical Stainless Steel Control Panel/Station (Keyed)	S	
In-car Digital Floor Indicator		O
Metal Car Station Pushbuttons With Halo Lighting	S	
Tactile Plates On Car Station	S	
Emergency Stop Button	S	
Emergency Alarm Button	S	
Handsfree Telephone		O
Melamine or MDF Wall Panels	S	
Unfinished Oak Veneer Wall Panels		O
Plastic Laminate Wall Panels		O
Stainless Steel Handrail (On Car Control Side Only)	S	
White Standard Eggcrate Ceiling With 4 Recessed Incandescent Down-Lights	S	
Clear Anodized Aluminum Trim (standard)	S	
Unfinished Plywood Sub-Floor	S	
Lamp Style Hall Position Indicators		O
Rubber Mat		O
Keyed Hall Call Stations (Manual Doors or Doors By Others)		O
Keyless Hall Call Stations (Manual Doors or Doors By Others)		O
Kwiklock Interlock (Doors By Others)		O
G.A.L. Interlock (Doors By Others)		O



PROLIFT SCL™
Standard Commercial Lift
Features & Options Summary
 Effective April 1, 2004

Cab/Entrance Features (continued)	Standard	Option
Pro-Auto Landing Entrance Door And Frame Assembly (Automatic Swing Door) Includes: 2 Hour UL/ULC Fire Rated Door, Zinc Wipe Coat Finish Concealed Auto Door Opener w/ Adjustable Open/Close Speed Swing Clear Opening Interior Aluminum Push Plate, Exterior Pull Handle Concealed Heavy Duty Stainless Steel BB Hinges Aluminum Frame Vision Panel Interior Aluminum Kickplate Pro-Auto Door Lock		O
Pro-Manual Landing Entrance Door And Frame Assembly (Manual Swing Door) Includes: 2 Hour UL/ULC Fire Rated Door, Zinc Wipe Coat Finish Two Speed Hydraulic Closure Aluminum Pull Handle Concealed Heavy Duty Stainless Steel BB Hinges Aluminum Frame Vision Panel Interior Aluminum Kickplate Pro Door Lock		O
Installation Features	Standard	Option
Elastomeric Bumpers	S	
Spring Buffers (24" minimum Pit Depth Required)	S	
Magnetic Floor Selection, Stopping and Re-leveling	S	
Final Upper Limit	S	
Negative Pressure Switch	S	
Variable Speed Pressure Compensated Proportional Valve	S	
Submersed Motor	S	
16' Rail Sections	S	
8' Rail Sections	S	
Final Drawings Included With Confirmed Order	S	
Operating Instruction Labels	S	
Hose 15' (With Flow Control Valve)		O
Hose 20' (With Flow Control Valve)		O
Hose 25' (With Flow Control Valve)		O
Flow Control Valve Only		O
Pipe Rupture Valve		O
Anchors For Hoistway Construction	S	
Lag Bolts		O
Through Bolts		O
Concrete Anchors		O
Split Cylinder (Automatically Selected When Travel Exceeds 32')		O
Temporary Run Button (Installation Tool)		O
Mechanical Rail Shoring Blocks	S	
Conductor Cable For Hoistway to Pump Wiring 40'	S	